2007 RESEARCH PROBLEM STATEMENT					
Problem Title: Evaluation of Optimal Traffic Monitoring Station Spacing on Fre	no.: 07.06-05				
Submitted By: Dave Kinnecom	Email: dkinnecom@utah.gov				
Project Champion: David Kinnecom, Traffic Management Engineer (UDOT or FHWA employee who needs this research done, will help the Research Division lead results. If the project gets prioritized at the UTRAC conference, a Champion Commitment Form					
1. Briefly describe the problem to be addressed. Performance measures on freeway travel are developed from traffic monitoring stations we several purposes: a) providing real-time speed on the website, which is color-coded based of times, which is now posted on variable message signs (and which, in the future, will be plather performance measure tracking. It is likely that other uses of speed data will be applied in the UDOT has typically installed traffic monitoring stations at one-half mile intervals. This stations would be used to detect incidents in real-time. For example, Illinois DOT had sure Now, the use of cameras and cell phones has made the use of speed data for incident determines are calculated to evaluate the trade-off between detector spacing and accuracy of estimates I space.	on three speed thresholds; b) calculation of real-time travel ced on UDOT's CommuterLink web site); and c) used for e future, such as determining travel time reliability. spacing dates back to theories that the traffic monitoring ch a system in place prior to the common use of cameras. ction less important. The problem to be determined in this				
2. Strategic Goal: Preservation Operation Capac	ity Safety (check all that apply)				
3A. List the research objective(s) to be accomplished: 1. Develop recommended criteria for placement of speed detection stations on freeway 3B. List the major tasks to accomplish the research objective(s): 1. Review existing UDOT data. 2. Develop an analytical model or method to calculate travel time and travel time relia 3. Using results of step 2, test alternative detector spacing to determine relationships b 4. Define recommended spacing.	Estimated person-hours: 1000 bility measures based on hypothetical detector spacing. etween accuracy and spacing.				
4. Estimate the cost of this research study including implementation effort (use person-hours from No. 3B): \$50,000					
5. Indicate type of research and/or development project this is Large: Research Project Development Project Small: Research Evaluation Experimental Feature New Other: (A small project is usually less than \$20,000 and shorter than 6 months) 6. Outline the proposed schedule (when do you need this done, and how will we estimate that this project will take one years to complete.	Product Evaluation Tech Transfer Initiative The get there:				
The estimate that this project will take one years to complete.					

2007 RESEARCH PROBLEM STATEMENT

7. What type of entity is best suited to perform this project (University, Consultant, UDOT Staff, Other Agency, Other)? A University					
		2 / 11 / 1		.1 1	
BB. Describe how this project w This will affect the location of tr	ill be implemented at UDOT. affic monitoring stations included in UDOT's IT	S systems.			
	enefit from the implementation of this pro- ne spacing (i.e. install fewer stations), there will be		beneficiaries will be.		
	nd obstacles as well as the strategies to ov nce the project consists of "mining" existing data		retical relationships fro	m the data.	
10. It distributes	I IDOT I III (c)		141: 0	*** (T. A. C.)	
for this study:	and non-UDOT) who are willing to partic	pate in the Techni	cai Advisory Comm	mee (TAC)	
<u>Name</u>	Organization / Division / Region	<u>Phone</u>	<u>Email</u>		
Dave Kinnecom Bryan Chamberlain Chris Siavrakas	UDOT Traffic Operations Center UDOT Traffic Operations Center UDOT Traffic Operations Center	887-3707 887-3723 887-3620			
Ciiris Siaviakas	ODOT Traine Operations Center	007-3020			